

USB SOCKET**NEW****DUAL USB SOCKETS W/AMP METER****P/No. A13-238AA****Features:**

- Rating : Input : 12/24V DC.
USB Output : 5V DC 2.4A + 2.4A, 2 ports
- Meter will flash when amp under 11.7(12v) or 22.8(24V).
- 3-digital LED display, available with red/green and blue
- With 6.3mm parallel terminals.
- Short circuit protection.
- Over current protection.
- Over-temperature protection.
- Suitable for most mobile phones and consumer electronic devices.
- Mounting hole : $\varnothing$ 29mm.
- Size : 37 dia x 49 (H) mm.

**WATERPROOF DUAL USB SOCKETS****P/No. A13-240****Features:**

- Rating :
Input : 12/24V DC.
USB Output : 5V DC 2.1A+2.1A max, 2 ports
- Pre-wired 18AWG wire.
- Reversed polarity protection.
- The knob must be tightened to ensure water-resistance..
- Mounting hole : Dia. 29.0mm
- Size : 37 dia x 67.0 (H) mm

IP 68**SLIDER DUAL USB SOCKETS****P/No. A13-249****Features:**

- Rating :
Input : 12/24V DC.
USB Output : 5V DC 3.1A max, 2 ports
- Pre-wired 20AWG wire.
- Reversed polarity protection..
- Over current protection
- Over-temperature protection
- Short circuit protection.
- Dual USB sockets with sliding dust cover.
- Lightguide onto the half are of both sides.
- Surface mounting with screws.
- Size : 63.8 X 47.8 x 20.4 (H) mm



*All the specifications are subject to change without notice.



www.sci.com.tw info@sci.com.tw

Headquarters:
TEL : 886-6-2532181
FAX : 886-6-2532633

Taipei Branch Office:
TEL : 886-2-25014062-4
FAX : 886-2-25040685

China Factory:
TEL : 86-752-3897988
FAX : 86-752-3897986
www.shinchin-sci.com

Hong Kong Branch:
TEL : 852-27939773
FAX : 852-27939830

Indonesia Factory:
TEL : 62-24-7627048
FAX : 62-24-7627047