

USB ADAPTER / USB SOCKET/ USB CHARGER**NEW****48W CAR CHARGER ADAPTER****P/No. A13-247AC****Features:**


- Rating : Input : 12/24V DC. Output :
Type A(QC3.0) : 5V 2.4A, 12W, 1 port.
Type-C(PD3.0) : 5V 9V/ 3A, 12V/2.5A, 15V/2A, 20V/1.8A, 1 port.
- Powerful on-the-go charging.
- USB-A output: 12W.max
USB-C output: 36W max
- Simultaneously charge two devices.
- Short circuit protection.
- Over current protection.
- Over-temperature protection.
- Suitable for most mobile phones and consumer electronic devices.
- Fits with $\varnothing$ 21mm socket.
- Size : 36.0 (L) x 28.0 (W) x 79.0(H) mm.

**USB SOCKETS****P/No. A13-245A & B****Features:**


- Rating : 12/24V DC. W/power indicator (blue LED)
- Pre-wired 18AWG wire.
- Reversed polarity protection.
- Dual sockets with waterproof cover.
- Mounting hole : 34 X 20 mm
- Size : 41 x 23 x 62 (H) mm



ITEM #	OUTPUT POWER	PORT 1	PORT 2
A13-245A	30.5W max	QC3.0 (5V 3A / 9V 2A / 12V 1.5A)	USB - 5V 2.5A
A13-245B	45W max	QC3.0 (5V 3A / 9V 2A / 12V 1.5A)	PD(5V 3A / 9V 2A / 12V 1.5A / 15V 1.2A / 20V 1.2A)

**VEHICLE USB CHARGER****W/ USB ADAPTER****P/No. A13-246****Features:**

- Rating : Input : 12/24V DC
USB Output : A13-232B - 5V DC 2.4A + 2.4A + 12V DC
A13-246-QC3.0 - 5V 3A / 9V 2A / 12V 1.5A
PD 45W- 5V 3A / 9V 3A / 12V 3A / 15V 3A / 20V 2A
- Extension cable : 1800mm.
- Over current protection, safety operation.
- When A13-232 is charging, A13-246 can be used too.
- Aluminum-alloy housing with good .heat dissipate
- Size : A13-232B - 42 x 42 x 73 (H) mm
A13-246 - 52 x 63 x 30 (H) mm



*All the specifications are subject to change without notice.



www.sci.com.tw info@sci.com.tw

Headquarters:
TEL : 886-6-2532181
FAX : 886-6-2532633

Taipei Branch Office:
TEL : 886-2-25014062-4
FAX : 886-2-25040685

China Factory:
TEL : 86-752-3897988
FAX : 86-752-3897986
www.shinchin-sci.com

Hong Kong Branch:
TEL : 852-27939773
FAX : 852-27939830

Indonesia Factory:
TEL : 62-24-7627048
FAX : 62-24-7627047